

Rittal – The System.

Faster – better – everywhere.



AX_IT 7647.400

Wall-mounted enclosure AX IT, Nano Data Center

State: 21/9/2026 (Source: www.rittal.com/in-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



AX_IT 7647.400 - Wall-mounted enclosure AX IT, Nano Data Center

Designer wall-mounted enclosure IT with 482.6 mm (19") swing frame for vertical and horizontal mounting.



Features

Model No.	AX IT 7647.400
Design	IT enclosure for use in industrial environments Pre-configured
Benefits	Pre-configured enclosure to accommodate 482.6 mm (19") IT components Compact design with maximum usable interior volume The welded enclosure structure guarantees a high level of physical protection (up to IP 54) Vertical (top) and horizontal (front) mounting for deep and shallow IT components Interchangeable door hinge Compatible with the AX wall-mounted enclosure system
Applications	IT enclosure for use in industrial environments
Material	Sheet steel
Surface finish	Enclosure and door: Dipcoat primed, powder-coated on the outside, textured paint Interior installation: Zinc-plated
Colour	RAL 7035

Features

Supply includes	Enclosure with hinged door Swing frame, 482.6 mm (19"), fitted Cam lock with 3 mm double-bit insert Gland plate
Units	11 U 4 U
Dimensions	Width: 600 mm Height: 800 mm Depth: 400 mm
Door hinge position	right, may be swapped to the left
Installation options	For vertical mounting For horizontal mounting
Note	Special variant available on request
Lock	Lock version: Cam lock with 3 mm double-bit lock insert Number of locks: 2
Protection category	Supports a protection category of up to IP 54, depending on the selected filter fan (optional)
Number of locks	2
Packs of	1 pc(s).
Net weight	35.5 kg
Gross weight	36 kg
Customs tariff number	94032080
Product description	AX IT Nano DC wall-mounted distributor, pre-assembled, installation height for components 565 mm vertical / 250 mm horizontal, with 482.6 mm (19") swing frame, WHD: 600x800x400 mm, with hinged door

Approvals

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity

Tender text

AX IT Nano DC, Article 7647.400

Rittal IT enclosure for industrial environments, Pre-assembled for 19" components, with swing frame. Material sheet steel, powder-coated finish, Color RAL 7035. Dimensions W600 x H800 x D400 mm. Includes hinged door with four breakouts and cam lock. Compatible with AX system, UL 508 compliant. Special versions available on request.